PUERTO RICO PORTS AUTHORITY

X63 REGIONAL AIRPORT / HURRICANE MARIA DISASTER RELIEF (DR-4339-PR) PROJECT #85447 / MPPA057 HUMACAO REGIONAL AIRPORT DR. HERMENEGILDO ORTIZ QUIÑONEZ AIRPORT, HUMACAO, PR

BID NO. 1-56

ADDENDUM NO. 4

TO ALL BIDDERS:

This addendum forms part of the Project Manual for Bid No. 1-56. Acknowledge receipt of this Addendum in the space provided on the bid proposal form. Failure to do so may subject Bidder to disqualification.

A. GENERAL – RESPONSE TO REQUESTS FOR FURTHER INFORMATION (RFI's) SUBMITTED BY BIDDERS

- Enclosed find a copy of the Letter from LOA Ingenieros CSP, the architectural and engineering contractor for this project, with ALL the answers and/or clarifications to various Requests for Further Information (RFI) submitted by Bidders for Bid 1-56. These revisions are dated October 22, 2025, for the Humacao Regional Airport project, Dr. Hermenegildo Ortiz Quiñonez (X63), Humacao, PR. See Attachment 1.
- 2. It is important to state that the PROPOSAL FORM for this Bid was revised and updated. The Proposal Form included in this Addendum No. 4 replaces in its entirety the one submitted with the original Project Manual. Please replace the document accordingly.

END OF ADDENDUM NO. 4

Romel Pedraza, PE
Assistant Executive Director
Planning, Engineering, Construction
& Environmental Affairs

October 22, 2025 San Juan, PR

ADDENDUM NO. 4

Attachment 1



October 22, 2025

Mr. Romel Pedraza-Claudio, PE
Assistant Executive Director for
Planning, Engineering and Construction
Attention: Mr. Roberto Rivera Medina
Engineering Bureau
Puerto Rico Ports Authority
64 Lindbergh Street
San Juan, Puerto Rico 00907

200400090

PUERTO RICO PORTS AUTHORITY (000-UEYUL-00)
ARCHITECTURAL AND ENGINEERING DESIGN SERVICES
HURRICANE MARÍA DISASTER RECOVERY-SECTOR 7

RE: PROJECT #85447/MPPA057-HUMACAO REGIONAL AIRPORT (HUC) RESPONSE TO RFIS

Dear Mr. Rivera:

We are submitting for your action the documents listed in the attachment. Please notify proposers.

Should you have any questions or need further information, you may me contact me at lortiz@loaingenieros.com or mobile 787-382-7782.

Cordially,

Ladislao Ortiz ., PE LOA Ingenieros, CSP

LO/JL

Enclosures (3)

c: E. Miranda-Gvelop W. Amaro-Gvelop

PUERTO RICO PORTS AUTHORITY (000-UEYUL-00) ARCHITECTURAL AND ENGINEERING DESIGN SERVICES HURRICANE MARÍA DISASTER RECOVERY-SECTOR 7 PROJECT #85447/MPPA057-HUMACAO REGIONAL AIRPORT (HUC)

BID NO. 1-56 REVISED BIDDING DOCUMENTS (22-OCT-2025)

	DC	DCUMENT	No. of Pages
	1.	Response to Questions	6
	2.	Instruction to Bidders, Page IB-12	1
	3/	Technical Specification, Section 074113.16 - Standing-Seam Metal Roof Panels	8
C	4.	Proposal Form	24
	5.	Revised Plans	13

END OF DOCUMENT

BID- 1.56 FOR CONSTRUCTION SERVICES TO RECOVERY PROJECTS UNDER THE

FEMA PUBLIC ASSISTANCE PROGRAM FOR DISASTER DR-4339-PR (Humacao Regional Airport (HUC) Humacao)

	Answers to Questions and Requests for Clarifications						
No.	Question	Proposer	Submission Date	Answer			
1	Específicamente el documento identificado como "DBE/ACDBE Certification of Good Faith Efforts entiendo que ese documento tal vez aplicaría para el contratista agraciado ya que contiene las palabras "I am" y "contractor selected for the PRPA project listed below"	Enviro-Tab, Inc.	10/1/25	Although its wording is for a selected contractor, the form shall be completed.			
2	Favor confirmar si el contrato es lump sum por la totalidad del trabajo, o si será por "unit price" según desglosado en el breakdown.	GVG Builders	10/8/25	Yes, the total project cost is lump sum. However, the funds provider requires the PRPA to itemize the project cost in pay items.			
3	Para las facilidades temporeras solicitadas, asumimos que la APPR costeara el costo de las utilidades de ambos vagones. Favor confirmar.	GVG Builders	10/8/25	No, unless otherwise instructed by PRPA. Refer to technical specifications, Section 015000-Temporary Facilities and Controls.			
4	Favor proveer planos estructurales para los trabajos de concretos de los edificios. De no estar disponibles, y para poder tener uniformidad en las propuestas de los contratistas, favor de indicar cuantas yardas de concreto se deberán asumir para cada estructura.	GVG Builders	10/8/25	Refer to Instruction Bidders, Article 16-Project Special Instructions, Section 16.2. The architectural drawings show dimensions to estimate concrete volumes.			
5	Favor confirmar quien será responsable por el pago de costos de conexión, vía libre, y otros de las utilidades (Luma, AAA, etc.). De ser el contratista, sugerimos se establezca un allowance para esto.	GVG Builders	10/8/25	The PRPA has allocated money for Luma utility. PRASA utilities shall not be affected by the project. Refer to Instruction Bidders, Article 16-Project Special Instructions, Section 16.1 for Luma money allocation.			
6	Favor proveer diseño y detalles para la remoción y reinstalación del Airfield Lights Voltage Regulator, además de su relocalización temporera y final.	GVG Builders	10/8/25	This item has been deleted from the scope of construction. The airfield lights voltage regulator will remain in place.			
7	En la hoja C006 habla de re-localizar el Airfield Lights Voltage Regulator, pero la 1D-1.1 habla de demoler/remover. Por favor aclarar. De relocalizar favor de proveer detalles de los trabajos en específico y planos para esto. Además, las hojas ES-1.0 y 1E1.1 hablan de que se reemplazará el equipo completamente lo cual no concuerda. De reemplazarse favor proveer más detalles del nuevo equipo a cotizar.	GVG Builders	10/8/25	Sheet 1D-1.1 has been deleted from the set. The Airfield Lights Voltage Regulator will not be relocated. Contractor shall replace existing Airfield Light Voltage Regulator with new Airfield Lights Voltage Regulator, Model L-829, 15kW output, 20-amp output class, 240VAC 60Hz input voltage.			
8	¿Las ventanas serán con celocitas en cristal o aluminio?	GVG Builders	10/8/25	The material of the louver windows is confirmed to be aluminum.			

9	Hoja 1D1.1 habla de demoler los pozos sépticos existentes, pero la C005 habla de demolerlos, favor confirmar cual aplica.	GVG Builders	10/8/25	The same questions are addressed for both sheets. Clarify question. However, sheet 1D-1.1 has been deleted from the set of plans.
10	¿El nuevo Hanger Door para el hangar 2 será manual o eléctrico?	GVG Builders	10/8/25	It will be mechanical (manual).
11	En el hangar #3 existe una puerta a remover? O la nueva puerta solicitada en la 3/3A2.1 es en un hueco existente donde no hay puerta?	GVG Builders	10/8/25	In Hangar #3, the existing door will be maintained. The notes currently shown on the drawings correspond to the doors of Hangar #2. This will be corrected in the drawings. An alternate door option was proposed for Hangar #2, and this will be included in the revised notes.
12	¿Encontramos discrepancias entre el Lighting Schedule en las hojas arquitectónicas y las eléctricas, cual domina?	GVG Builders	10/8/25	Refer to General Notes 16 and 17 in sheet GR-003.
13	En el artículo 16.3 del Project Manual habla de un baño nuevo para el hangar H2. De ser requerido favor proveer detalles para el mismo.	GVG Builders	10/8/25	Bathroom and plumbing services (i.e., water sewage) have been deleted from scope. Refer to Instruction to Bidders, revised page IB-12 attached.
14	Favor confirmar que APPR ya tiene permisos para construcción, y el contratista sólo levantará el permiso de construcción según APPR lo tenga ya aprobado. Además, favor confirmar que el contratista sólo proveerá los diseños estructurales según indicados.	GVG Builders	10/8/25	No, it does not. Contractor will provide signed and sealed structural designs in conformity with PR Building Codes-2018 and the Joint Regulation requirements including Special Electronic Stamps as appropriate. The PRPA will file for the construction permit upon receipt of Specialist Certification, EDE (Special Digital Stamps) and proof of CIAPR/CAAPR membership with engineer or architect valid certificate.
15	¿Cuánto es el tiempo de diseño y construcción? ¿El tiempo de permisos será tomado en consideración dentro de este tiempo o será aparte? De ser incluido en este tiempo, favor confirmar cuántos días serían separados para el proceso de permisos	GVG Builders	10/8/25	Time will remain unchanged.
16	El plano no marca pavement markings excepto en el estacionamiento. Pero el bid form tiene 925 lm. Por favor aclarar.	GVG Builders	10/8/25	Sheets C-004 and C-007 have been revised showing limit of pavement markings.

	Teach and the second of the se	0.40 =		<u> </u>
17	Muchas de las partidas y cantidades en el proposal form	GVG Builders	10/8/25	Quantities were verified and Proposal Form updated.
	no guardan proporción con lo mostrado en los planos.			
	Por ejemplo, en aceras nosotros calculamos mucho más			
	de 90 sm, en encintados mucho menos de 155 lm, en			
	seeding tenemos mucho más de 540 sm, las lámparas			
	no cuadran (si nos dejamos llevar por la hoja eléctrica),			
	la partida de Accoustic Tiles esta repetida varias veces,			
	la cantidad de railings es menor a la indicada, la partida			
	de Wall Tile esta repetida, Baby Changing station hay 1			
	solo no 3 como indica el bid form, Soap Disp. hay solo 3			
	no 5, LED Mirror son 2 no 1, no entendemos a que se			
	refiere la partida SS-1 Solid Surface (27 EA), el bid form			
	tiene 1 televisor y un mobiliario que no aparece en los			
	planos, las cantidades de concretos no concuerdan			
	(ejemplo hay 156 cy para parapetos), Overflow Drains el			
	plano solo indica 1, no entendemos a que se refiere la			
	partida 91 Adjustments to Prepa, Postes de 45ft			
	entendemos que hay solo 8 no 9, los PREPA Distribution			
	Standards no necesariamente concuerdan/aplican al			
	igual que la cantidad de cablería, el item 108 de Power			
	Substation no se indica en los planos, no vemos partida			
	para los trabajos en los hangares 2 (estabilización,			
18	We would like to formally request an extension of the	SLSCO LTD (SLSCO, LLP)	10/10/25	Dates in Advertisement for Bid will remain unchanged.
	proposal's submission deadline to allow additional time			
	for our suppliers to provide the necessary quotes			
	required to complete our submission.			
19	In the set of construction drawings, there are no	SLSCO LTD (SLSCO, LLP)	10/10/25	Plumbing plans for Terminal Building are included. Hangar 2 does
	plumbing drawings. Please provide.			not have plumbing Scope of Work.
20	In the set of construction drawings, there are no HVAC	SLSCO LTD (SLSCO, LLP)	10/10/25	HVAC plans for Terminal Building are included.
	drawings. Please provide.			
21	In the set of construction drawings, there are no	SLSCO LTD (SLSCO, LLP)	10/10/25	Refer to Instruction Bidders, Article 16-Project Special
	structural drawings. Please provide.			Instructions, Section 16.2.
22	In the set of construction drawings, the civil engineering	SLSCO LTD (SLSCO, LLP)	10/10/25	The soil improvements are shown in sections A and B for each
	drawings do not show the soils improvement design as			structure in Sheet C-007 with the aggregate layers, thickness and
	described in the soils report and on sheet C-007 which			type of reinforcement as recommended in the geotechnical report.
	recommends a mat foundation over a reinforced granular			The contractor shall submit to PRPA products and materials
	mattress for both new buildings. Please provide the soils			information for review and approval.
	Linearus consent decime of the formedations of heath buildings			ı

23	The architectural drawings show that the new Terminal Bldg. will be constructed using Structural Concrete Insulated Panels (SCIP) and a "Technical Manual & Installation Guide" for this system is provided in the project manual. However, some of the architectural plans (and all of the structural plans since they are currently nonexistent) lack details specific to this project. Please provide coordinated architectural and structural details necessary to build this project.	SLSCO LTD (SLSCO, LLP)	10/10/25	Refer to Instruction Bidders, Article 16-Project Special Instructions, Section 16.2.
24	Spec section 74113.16 (standing seam metal roof panels) to be used on the new hangar building has conflicting information concerning thickness of panel. Please verify gauge of roof panel and specify the desired roof panel.	SLSCO LTD (SLSCO, LLP)	10/10/25	The specified roof system for the new hangar building — including both the roof and the wall assemblies — shall consist of PAC-CLAD's Precision Series HWP (High Wind Panel), or approved equal, fabricated from 22-gauge G-90 galvanized steel with a smooth finish, with clip installation and 16-inch on-center profile in Hemlock Green. This panel system has been selected for use across both roof and wall surfaces to ensure material consistency, architectural uniformity, and superior performance under the high wind load and weather exposure conditions of the project site.
24	We do not see the specification for the metal wall system (exterior wall) for the hangar building in the specifications or drawings. Please verify the desired wall panel and gauge.	SLSCO LTD (SLSCO, LLP)	10/10/25	Refer to Response No. 24, where it is confirmed that the roof and wall assemblies will be constructed using the same material.
25	Please clarify the structural HSS members used in the railing and guardrail design on sheet 1A-5.2. The specified HSS sizes of 1" x 4" and ½" x 3" are not standard dimensions.	SLSCO LTD (SLSCO, LLP)	10/10/25	Due to observations received during the bidding phase, it is specified that the handrails shall be fabricated from aluminum, using 6061/T1 rectangular tube profiles with a thickness of 1/8", dimensions of 1" x 3" for general frame and 1" x 2" for vertical elements. The material and dimensions shall comply with applicable tolerances and standards to ensure structural strength and durability.
26	Please provide a specification section for the hangar doors shown on the plans (hangers 2 and 3). The only specification provided for specialty doors is for "Overhead Sectional Doors" which will be used at the terminal bldg.	SLSCO LTD (SLSCO, LLP)	10/10/25	Clarification Note: Please be advised that Hangar 3 is not included within the scope of the hangar door replacement work. As an alternative to the existing door at Hangar 2, the PowerLift Hydraulic Doors system is proposed, with dimensions of 42' x 16, manufactured by PowerLift Door, or approved equal. The relevant sheet will be reviewed in detail to verify and clarify any potential confusion regarding the scope, ensuring that the documentation accurately reflects the buildings and elements included in the project.

27	Because of the curved roof at hangar 3, using an overhead sectional door is not practical. But for new building 2, can an alternate be an overhead sectional door in lieu of the folding panel doors as shown on sheet 2A-3.1?	SLSCO LTD (SLSCO, LLP)	10/10/25	The type of hangar shown (arch and gable) are for illustration of the options available locally that the contractor may opt. As well, the contractor may select other types of doors if it complies with the minimum opening dimensions and the Puerto Rico Building Codes-2018. The products shall be submitted to the PRPA for review and approval.
28	South Elevation on sheet 3A-2.1 indicates the new hangar doors. Please provide more information about how the doors will open, stack, etc. Please include overall dimensions of each door leaf as shown. Is the architect open to suggestions as per the hangar door	SLSCO LTD (SLSCO, LLP)	10/10/25	For this hangar #3, the existing doors shall remain. An alternative option for the hangar doors was added specifically for Hangar 2. These notes are under review and will be corrected and included in the appropriate location in the drawing sheets.
29	Please provide specifications for the signage that needs to be replaced or included in the design including the lettering on the Building's Front Facade.	SLSCO LTD (SLSCO, LLP)	10/10/25	Site signage is included in sheet C-009. The building's front signage shall consist of individual letters fabricated from painted aluminum, with the typeface Bahnschrift Light. The letters shall have a matte black finish and a height of 7 inches. Each letter shall be mounted 1 inch away from the wall, maintaining a uniform spacing to create a floating shadow effect. This mounting shall be achieved using spacers or stud-mounted pins with bushings. The fastening system must ensure long-term durability, resistance to corrosion (especially in coastal environments), and must be concealed or minimally visible from the front. The final installation shall align with the architectural intent and comply with local building codes and the applicable wind-load requirements.
30	The lighting schedule in the Architectural Drawings and the lighting schedule in the Electrical drawings don't match. Which Schedule should we use to quote?	SLSCO LTD (SLSCO, LLP)	10/10/25	Refer to General Notes 16 and 17 in sheet GR-003.
31	Please confirm if the Repairs for the Existing Hangars will include Paint and or Weatherproofing.	SLSCO LTD (SLSCO, LLP)	10/10/25	Repair work for the existing hangars shall include painting only; no weatherproofing measures are included as part of this scope.
32	Please provide hardware schedule for Doors.	SLSCO LTD (SLSCO, LLP)	10/10/25	Door hardware specifications have been added.
33	Could not find the electrical design for the Lightning Suppression System on the Roof of the Terminal Building. Please provide.	SLSCO LTD (SLSCO, LLP)	10/10/25	An allowance has been allocated for lightning protection.
34	Provide copy of electrical drawings endorsed by LUMA.	SLSCO LTD (SLSCO, LLP)	10/10/25	At the present, the project is under review by Luma.

35	Provide design for the Solar Panel mounting Brackets.	SLSCO LTD (SLSCO, LLP)	10/10/25	The PV system shall be considered as part of the structural design. Refer to Instruction Bidders, Article 16-Project Special Instructions, Section 16.2.
36	Since the terminal building is SCIP, will there be additional insulation required?	SLSCO LTD (SLSCO, LLP)	10/10/25	In addition to the SCIP system, no other type of insulation is required for the building.
37	The two hanger door manufacturers mentioned on the drawings are based in the UK. Since this job is "Buy American" will the contractor be allowed to purchase from them?	SLSCO LTD (SLSCO, LLP)	10/10/25	The products allowed for this project must strictly comply with the "Buy American" requirements. In accordance with this mandate, an alternate product is presented that meets the expected quality and performance standards. To replace the initially proposed product, the PowerLift Hydraulic Doors system is proposed, with dimensions of 42' x 16, manufactured by PowerLift Door, or approved equal. Installation of the alternate product shall be carried out in accordance with the manufacturer's recommendations, ensuring compliance with local building codes, safety requirements, and project specifications. Additionally, compatibility with existing systems shall be verified to ensure integrated and efficient operation.
38	Please provide the weight of the airplane that will be housed in New hangar 2.	SLSCO LTD (SLSCO, LLP)	10/10/25	Use FAA ADG I aircraft for design.

5	Financial Capacity	The Bidder demonstrated that it has access to, or has available, liquid assets, unencumbered real assets, lines of credit, and other financial means sufficient to meet the construction cash flow requirements for a minimal amount of: \$1,000,000.	
6	Past Performance	The Prime Contractor does not have any default, or unjustified delays in meeting completion date on previous projects. Failure to disclose information will result in rejection of the bids.	

ARTICLE 16 – PROJECT SPECIAL INSTRUCTIONS

- 16.1 A money allocation is available for Luma connection fees and other charges such as temporary service interruption (*via libre*). The PRPA will reimburse to the contractor expenses incurred upon presentation of invoices issued by Luma. No profit or overhead under this pay item will be reimbursed.
- 16.2 The material proposed for the new terminal building is novel construction, of concrete and structural concrete insulated panels (SCIP) or similar product available by manufacturers and suppliers in Puerto Rico. The Proposer shall consider in its proposal the cost of structural design of this building by a licensed architect or licensed engineer in Puerto Rico. The geotechnical report for this project is available and is made part of this manual.
- 16.3 Hangar H-2 is pre-engineered and prefabricated galvanized steel roof & walls building similar to the suggested types shown in the drawings. The proposed building shall include a large door to fit a small aircraft with the dimensions shown in the plans and at least one (1) door for a person to access the building from the outside. In addition, this item shall consider the footing slab, lighting, electrical distribution; ene (1) bathroom with water closet and sink; domestic sewer connection to the existing septic tank and the plumbing of the bathroom for future water service. The design of this building shall be certified by a licensed architect or licensed engineer in Puerto Rico.
- 16.4 The Proposer shall consider in the cost proposal the certifications of design documents (plans, specifications and specialist certification form) and the Special Digital Stamp (EDE in its Spanish acronym) from the *Colegio de Ingenieros y Agrimensores de Puerto Rico* items 16.1 and 16.2 in compliance with Puerto Rico Joint Regulation for the Evaluation and Issuance of Permits Related to Development, Land Use and Business Operations (Joint Regulation) and Puerto Rico Building Codes (2018 or latest issue). The PRPA will review that the design is in line with their intention on the type of building construction and that the design documents follow regulations and building codes. Upon completion reviewing of all documents, the PRPA will file for and will obtain the construction permit for the works.

SECTION 074113.16 - STANDING-SEAM METAL ROOF PANELS

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Standing-seam metal roof panels.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Shop Drawings: Include fabrication and installation layouts of metal panels; details of edge conditions, joints, panel profiles, corners, anchorages, attachment system, trim, flashings, closures, and accessories; and special details.
- C. Samples: For each type of metal panel indicated.

1.3 INFORMATIONAL SUBMITTALS

- A. Product test reports.
- B. Warranties: Sample of special warranties.

1.4 CLOSEOUT SUBMITTALS

A. Maintenance data.

1.5 QUALITY ASSURANCE

- A. Installer Qualifications: An entity that employs installers and supervisors who are trained and approved by the manufacturer.
- B. UL-Certified, Portable Roll-Forming Equipment: UL-certified, portable roll-forming equipment capable of producing metal panels warranted by manufacturer to be the same as factory-formed products. Maintain UL certification of portable roll-forming equipment for duration of work.

1.6 WARRANTY

A. Special Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace components of metal panel systems that fail in materials or workmanship within specified warranty period.

- 1. Warranty Period: **Two** years from date of Substantial Completion.
- B. Special Warranty on Panel Finishes: Manufacturer's standard form in which manufacturer agrees to repair finish or replace metal panels that show evidence of deterioration of factory-applied finishes within specified warranty period.
 - 1. Finish Warranty Period: 20 years from date of Substantial Completion.
- C. Special Weathertightness Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace standing-seam metal roof panel assemblies that fail to remain weathertight, including leaks, within specified warranty period.
 - 1. Warranty Period: **20** years from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 CLADDING SYSTEM / STANDING SEAM AND RELATED MATERIALS

A. Cladding System / Standing Seam:

Basis of Design Product: Subject to compliance with requirements, provide **Pac-Clad** products that meet the following specifications:

- 1- PRECISION SERIES WALL PANELS HWP (or approved equal) metal roof field-seamed panels.
- B. Insulation:

Basis of Design Product: Subject to compliance with requirements, provide **Prodex.** Products that meet the following specifications:

2- **AD5 Reflective Thermal Insultation** (or approved equal) – Aluminum foil. Polyethyelene foam and aluminum foil.

2.2 PERFORMANCE REQUIREMENTS

- A. Energy Performance: Provide roof panels that are listed on the EPA/DOE's ENERGY STAR "Roof Product List" for **low**-slope roof products.
- B. Energy Performance: Provide roof panels according to one of the following when tested according to CRRC-1:
 - 1. Three-year, aged solar reflectance of not less than **0.55** and emissivity of not less than **0.75**.
 - 2. Three-year, aged Solar Reflectance Index of not less than **64** when calculated according to ASTM E1980.
- C. Structural Performance: Provide metal panel systems capable of withstanding the effects of the following loads, based on testing according to ASTM E1592:
 - 1. Wind Loads: As indicated on Drawings.
 - 2. Other Design Loads: As indicated on Drawings.

- D. Air Infiltration: Air leakage of not more than 0.06 cfm/sq. ft. (0.3 L/s per sq. m) when tested according to ASTM E1680 or ASTM E283 at the following test-pressure difference:
 - 1. Test-Pressure Difference: 6.24 lbf/sq. ft. (300 Pa).
- E. Water Penetration under Static Pressure: No water penetration when tested according to ASTM E1646 or ASTM E331 at the following test-pressure difference:
 - 1. Test-Pressure Difference: 6.24 lbf/sq. ft. (300 Pa).
- F. Hydrostatic-Head Resistance: No water penetration when tested according to ASTM E2140.
- G. Wind-Uplift Resistance: Provide metal roof panel assemblies that comply with UL 580 for wind-uplift-resistance class indicated.
 - 1. Uplift Rating: UL 90.
- H. FM Global Listing: Provide metal roof panels and component materials that comply with requirements in FM Global 4471 as part of a panel roofing system and that are listed in FM Global's "Approval Guide" for Class 1 or noncombustible construction, as applicable. Identify materials with FM Global markings.
 - 1. Fire/Windstorm Classification: Class 1A-120.
 - 2. Hail Resistance: MH.
- I. Thermal Movements: Allow for thermal movements from ambient and surface temperature changes by preventing buckling, opening of joints, overstressing of components, failure of joint sealants, failure of connections, and other detrimental effects. Base calculations on surface temperatures of materials due to both solar heat gain and nighttime-sky heat loss.
 - 1. Temperature Change (Range): 120 deg F (67 deg C), ambient; 180 deg F (100 deg C), material surfaces.

2.3 STANDING-SEAM / METAL ROOF PANELS

- A. Provide factory-formed metal roof panels designed to be installed by lapping and interconnecting raised side edges of adjacent panels with joint type indicated and mechanically attaching panels to supports using concealed clips in side laps. Include clips, cleats, pressure plates, and accessories required for weathertight installation.
 - 1. Steel Panel Systems: Unless more stringent requirements are indicated, comply with ASTM E1514.
- B. The Precision Series Wall Panels are concealed-fastener metal wall systems engineered for high performance and refined architectural expression. Fabricated from G90 galvanized steel, the panels deliver outstanding structural rigidity, corrosion resistance, and long-term durability in both exterior and interior applications.

Designed for horizontal or vertical installation, the system features factory-formed interlocking joints that provide a continuous, uniform surface while allowing for controlled

thermal movement and superior weather resistance. Precision engineering ensures consistent panel alignment and tight joint tolerances.

Panels are available in **flat, ribbed, and reveal profiles** to accommodate a wide range of design aesthetics and functional requirements. Finishes include **Kynar 500®/Hylar 5000® PVDF coatings**, offering exceptional color retention and resistance to UV degradation, chalking, and fading.

C.

- 1. Basis of Design: PRECISION SERIES WALL PANELS by Pac-Clad.
- 2. Metallic-Coated Steel Sheet: Zinc-coated (galvanized) steel sheet complying with ASTM A653/A653M, G90 (Z275) coating designation. Prepainted by the coil-coating process to comply with ASTM A755/A755M.
 - a. Nominal Thickness: 22 gauge
 - b. Exterior Finish: Two-coat fluoropolymer.
 - c. Color: As selected by Architect from manufacturer's full range.
- 3. Clips: **Two-piece floating** to accommodate thermal movement.
 - a. Material: 0.064-inch- (1.63-mm-) nominal thickness, zinc-coated (galvanized) or aluminum-zinc alloy-coated steel sheet.
- 4. Joint Type: **Double folded**.
- 5. Panel Coverage: 16 inches (406 mm).
- 6. Panel Height: 7/8 inches (22 mm).

2.4 UNDERLAYMENT MATERIALS

Self-adhering, high-temperature underlayment may be applied only at eaves, valleys, and other areas vulnerable to leakage, with felt applied over the remainder of the roof; or underlayment may be applied over the entire roof area.

- A. Self-Adhering, High-Temperature Underlayment: Provide self-adhering, cold-applied, sheet underlayment, a minimum of 30 mils (0.76 mm) thick, consisting of slip-resistant, polyethylene-film top surface laminated to a layer of butyl or SBS-modified asphalt adhesive, with release-paper backing. Provide primer when recommended by underlayment manufacturer.
 - 1. Thermal Stability: Stable after testing at 240 deg F (116 deg C); ASTM D1970.
 - 2. Low-Temperature Flexibility: Passes after testing at minus 20 deg F (29 deg C); ASTM D1970.

If not using self-adhering, high-temperature underlayment over the entire roof area.

B. Felt Underlayment: ASTM D226/D226M, Type II (No. 30), asphalt-saturated organic felts.

Slip Sheets can be used to separate metal roof panels from underlayment if required by manufacturer.

C. Slip Sheet: Manufacturer's recommended slip sheet, of type required for application.

2.5 ROOF INSULATION

Shall consist of one (or more) reflective thermal insulation base layer(s) inserted between the substrate below and the standing seam metal roofing above. It shall be provided in the thicknesses and taper required to achieve an "R" value of 20 and complying with:

A. Reflective Thermal Insulation Layer:

Basis of Design Product: Subject to compliance with requirements, provide **Prodex** products that meet the following specifications (Other products may be submitted for approval):

- 1. Product: AD5 (or approved equal) Aluminum foil. Polyethyelene foam and aluminum foil.
- 2. Thickness: 0.19" thickness, total thickness to meet specified insulation system thermal resistance 'R' value.
- 3. Dimensions: 4' x 4' boards, as per manufacturer's recommendations for system.
- 4. Meets or exceeds ASTM C1224 for corrosiveness, pliability, humidity resistance and operating temperatures.
- 5. Meets or exceeds ASTM C1338 for resistance to mold growth.

2.6 MISCELLANEOUS MATERIALS

- A. Miscellaneous Metal Subframing and Furring: ASTM C645; cold-formed, metallic-coated steel sheet, ASTM A653/A653M, G90 (Z275 hot-dip galvanized) coating designation or ASTM A792/A792M, Class AZ50 (Class AZM150) coating designation unless otherwise indicated. Provide manufacturer's standard sections as required for support and alignment of metal panel system.
- B. Panel Accessories: Provide components required for a complete, weathertight panel system including trim, copings, fasciae, mullions, sills, corner units, clips, flashings, sealants, gaskets, fillers, closure strips, and similar items. Match material and finish of metal panels unless otherwise indicated.
 - 1. Closures: Provide closures at eaves and ridges, fabricated of same metal as metal panels.
 - 2. Backing Plates: Provide metal backing plates at panel end splices, fabricated from material recommended by manufacturer.
 - 3. Closure Strips: Closed-cell, expanded, cellular, rubber or crosslinked, polyolefin-foam or closed-cell laminated polyethylene; minimum 1-inch- (25-mm-) thick, flexible closure strips; cut or premolded to match metal panel profile. Provide closure strips where indicated or necessary to ensure weathertight construction.
- C. Flashing and Trim: Provide flashing and trim formed from same material as metal panels as required to seal against weather and to provide finished appearance. Locations include, but are not limited to, eaves, rakes, corners, bases, framed openings, ridges, fasciae, and fillers. Finish flashing and trim with same finish system as adjacent metal panels.

- D. Gutters and Downspouts: Formed from same material as roof panels according to SMACNA's "Architectural Sheet Metal Manual." Finish to match **metal roof panels** and **roof fascia and rake trim**.
- E. Roof Curbs: Fabricated from same material as roof panels, **0.048-inch (1.2-mm)** nominal thickness; with bottom of skirt profiled to match roof panel profiles and with welded top box and integral full-length cricket. Fabricate curb subframing of **0.060-inch- (1.52-mm-)** nominal thickness, angle-, C-, or Z-shaped steel sheet. Fabricate curb and subframing to withstand indicated loads of size and height indicated. Finish roof curbs to match metal roof panels.
- F. Panel Fasteners: Self-tapping screws designed to withstand design loads.
- G. Panel Sealants: Provide sealant type recommended by manufacturer that are compatible with panel materials, are nonstaining, and do not damage panel finish.
 - 1. Sealant Tape: Pressure-sensitive, 100 percent solids, gray polyisobutylene compound sealant tape with release-paper backing; 1/2 inch (13 mm) wide and 1/8 inch (3 mm) thick
 - 2. Joint Sealant: ASTM C920; as recommended in writing by metal panel manufacturer.
 - 3. Butyl-Rubber-Based, Solvent-Release Sealant: ASTM C1311.

2.7 FABRICATION

- A. Fabricate and finish metal panels and accessories at the factory, by manufacturer's standard procedures and processes, as necessary to fulfill indicated performance requirements demonstrated by laboratory testing. Comply with indicated profiles and with dimensional and structural requirements.
- B. On-Site Fabrication: Subject to compliance with requirements of this Section, metal panels may be fabricated on-site using UL-certified, portable roll-forming equipment if panels are of same profile and warranted by manufacturer to be equal to factory-formed panels. Fabricate according to equipment manufacturer's written instructions and to comply with details shown.
- C. Provide panel profile, including major ribs and intermediate stiffening ribs, if any, for full length of panel.
- D. Fabricate metal panel joints with factory-installed captive gaskets or separator strips that provide a weathertight seal and prevent metal-to-metal contact, and that minimize noise from movements.
- E. Sheet Metal Flashing and Trim: Fabricate flashing and trim to comply with manufacturer's recommendations and recommendations in SMACNA's "Architectural Sheet Metal Manual" that apply to design, dimensions, metal, and other characteristics of item indicated.

2.8 FINISHES

A. Panels and Accessories:

- 1. Two-Coat Fluoropolymer: [AAMA 621] [AAMA 2605]. Fluoropolymer finish containing not less than 70 percent polyvinylidene fluoride (PVDF) resin by weight in both color coat and clear topcoat.
- 2. Concealed Finish: White or light-colored acrylic or polyester backer finish.

PART 3 - EXECUTION

3.1 PREPARATION

A. Miscellaneous Supports: Install subframing, furring, and other miscellaneous panel support members and anchorages according to ASTM C754 and metal panel manufacturer's written recommendations.

3.2 INSTALLATION OF UNDERLAYMENT

- A. Self-Adhering Sheet Underlayment: Apply primer if required by manufacturer. Comply with temperature restrictions of underlayment manufacturer for installation. Apply at locations indicated **below**, wrinkle free, in shingle fashion to shed water, and with end laps of not less than 6 inches (152 mm) staggered 24 inches (610 mm) between courses. Overlap side edges not less than 3-1/2 inches (90 mm). **Extend underlayment into gutter trough.** Roll laps with roller. Cover underlayment within 14 days.
 - 1. Apply over the entire roof surface.
 - a. Roof perimeter for a distance up from eaves of 36 inches (914 mm) beyond interior wall line.
 - b. Valleys, from lowest point to highest point, for a distance on each side of 18 inches (460 mm). Overlap ends of sheets not less than 6 inches (152 mm).
 - c. Rake edges for a distance of 18 inches (460 mm).
 - d. Hips and ridges for a distance on each side of 12 inches (305 mm).
 - e. Roof-to-wall intersections for a distance from wall of 18 inches (460 mm).
 - f. Around dormers, chimneys, skylights, and other penetrating elements for a distance from element of 18 inches (460 mm).
- B. Felt Underlayment: Apply at locations indicated **below**, in shingle fashion to shed water, and with lapped joints of not less than 2 inches (50 mm).
 - 1. Apply over the entire roof surface.
- C. Slip Sheet: Apply slip sheet over underlayment before installing metal roof panels.
- D. Flashings: Install flashings to cover underlayment to comply with requirements specified in Section 076200 "Sheet Metal Flashing and Trim."

3.3 INSTALLATION OF STANDING SEAM METAL ROOF PANELS

- A. Standing-Seam Metal Roof Panel Installation: Fasten metal roof panels to supports with concealed clips at each standing-seam joint at location, spacing, and with fasteners recommended in writing by manufacturer.
 - 1. Install clips to supports with self-tapping fasteners.
 - 2. Install pressure plates at locations indicated in manufacturer's written installation instructions.
 - 3. Seamed Joint: Crimp standing seams with manufacturer-approved, motorized seamer tool so clip, metal roof panel, and factory-applied sealant are completely engaged.
 - 4. Watertight Installation:
 - a. Apply a continuous ribbon of sealant or tape to seal joints of metal panels, using sealant or tape as recommend in writing by manufacturer as needed to make panels watertight.
 - b. Provide sealant or tape between panels and protruding equipment, vents, and accessories.
 - c. At panel splices, nest panels with minimum 6-inch (152-mm) end lap, sealed with sealant and fastened together by interlocking clamping plates.
- B. Accessory Installation: Install accessories with positive anchorage to building and weathertight mounting, and provide for thermal expansion. Coordinate installation with flashings and other components.
- C. Flashing and Trim: Comply with performance requirements, manufacturer's written installation instructions, and SMACNA's "Architectural Sheet Metal Manual." Provide concealed fasteners where possible, and set units true to line and level as indicated. Install work with laps, joints, and seams that will be permanently watertight and weather resistant.

3.4 CLEANING AND PROTECTION

A. Remove temporary protective coverings and strippable films, if any, as metal panels are installed, unless otherwise indicated in manufacturer's written installation instructions. On completion of metal panel installation, clean finished surfaces as recommended by metal panel manufacturer. Maintain in a clean condition during construction.

END OF SECTION 074113.16

GOVERNMENT OF PUERTO RICO PUERTO RICO PORTS AUTHORITY

PUERTO RICO HURRICANE MARÍA DISASTER RELIEF (DR-4339-PR) PROJECT #85447/MPPA057 HUMACAO REGIONAL AIRPORT (HUC) HUMACAO, PUERTO RICO

BID NO. 1-56

PROPOSAL

Executive Director		
Puerto Rico Ports Authority		
PO Box 362829		
San Juan, Puerto Rico 00936-2829		
The undersigned (hereinafter called "Bidder") in construction project, Puerto Rico Hurricane M#85447/MPPA057 Humacao Regional Airport (HUC), specifications and related documents, the site of the conditions surrounding the construction of the propose labor, hereby proposes to furnish all labor, materials, ein accordance with the Contract Documents, within the	María Disaster Relief (DR-4339-PR), Pro Humacao, Puerto Rico, having examined the pla he proposed work, and being familiar with all sed project, including the availability of materials a equipment and supplies, and to construct the pro	ject ans, the and ject
	dollars (\$	_).
The Bidder presents the breakdown below with appropriate of bids.	eximate quantities for the purpose of the comparis	son

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
1	G-1.1	MOBILIZATION (NOT TO EXCEED 10% OF TOTAL BID AMOUNT)	LS	1		
2	G-1.2	SAFETY, SECURITY, AND MAINTENANCE OF AIRPORT OPERATION (Price in Words)	LS	1		

2025

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
3	G-1.3	MUNICIPAL TAX AND PATENTS (SUM OF ITEMS 1-117 MULTIPLIED BY 0.06) WILL BE PAID AS PER INVOICE (Price in Words)	LS	1		
4	G-2.1	CONSTRUCTION SURVEY (Price in Words)	LS	1		
5	G-2.2	TEMPORARY AIR AND WATER POLLUTION, SOIL EROSION, AND SILTATION CONTROL (Price in Words)	LS	1		
6	G-2.3	MAINTENANCE AND PROTECTION OF TRAFFIC (Price in Words)	LS	1		
7	C-1.1	SITE CLEARING (approx. 769 SqM) (Price in Words)	LS	1		
8	C-1.2	DEMOLITION (Price in Words)	LS	1		

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
9	C-1.3	MAIN TERMINAL AND HANGAR 2 EARTH FILL AND EMBANKMENT STABILIZATION	LS	1		
		(Price in Words)				
10	C-2.1	AGGREGATE BASE COURSE (approx. 9 CuM)	LS	1		
		(Price in Words)				
11	C-2.2	LEAN CONCRETE BASE (approx. 8 SqM)	LS	1		
		(Price in Words)				
12	C-2.3	HOT PLANT-MIX BITUMINOUS PAVEMENT (approx. 430 TON)	LS	1		
13	C-2.4	(Price in Words) FULL DEPTH REMOVAL OF BITUMINOUS PAVEMENT (approx. 7 CuM)	LS	1		
14	C-2.5	2" (0.05 MTS.) COLD MILLING OF BITUMINOUS CONCRETE PAVEMENT (approx. 3,136 SqM)	LS	1		

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
15	C-3.1	CHAIN-LINK FENCE, TYPE-B (approx. 32 LnM) (Price in Words)	LS	1		
16	C-3.2	CHAIN-LINK GATE, TYPE-B, ONE LEAF, WIDTH= 6.0 FT. (approx. 1 EA) (Price in Words)	LS	1		
17	C-3.2	CHAIN-LINK GATE, TYPE-B, TWO LEAVES, WIDTH= 14.0 FT. (approx. 1 EA) (Price in Words)	LS	1		
18	C-3.3	CONCRETE SIDEWALK (approx. 170 SqM)	LS	1		
19	C-3.4	CONCRETE CURB, TYPE D (approx. 155 LnM) (Price in Words)	LS	1		
20	C-3.5	RECONSTRUCTION OF CONCRETE SHALLOW GUTTER (approx. 22 LnM) (Price in Words)	LS	1		

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
21	C-3.7	TACTILE WARNING SURFACING (approx. 1 EA) ———————————————————————————————————	LS	1		
22	C-4.1	TOPSOIL (approx. 17 CuM) (Price in Words)	LS	1		
23	C-4.2	SEEDING (HYDROSEEDING) (approx. 540 SqM) (Price in Words)	LS	1		
24	C-4.3	SODDING (ZOYSA MANILA) (approx. 85 SqM) (Price in Words)	LS	1		
25	C-5.1	TRAFFIC SIGNS (approx. 2 EA) (Price in Words)	LS	1		
26	C-5.2	THERMOPLASTIC PAVEMENT MARKINGS STRIPE, WHITE approx. 925 LnM) (Price in Words)	LS	1		

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
27	C-5.3	PAINTED PAVEMENT MARKINGS (approx. 130 LnM)	LS	1		
		(Price in Words)				
28	SCP-01	EXTERIOR AND INTERIOR STRUCTURAL CONCRETE INSULATED PANELS (SCIP) WALLS (approx. 86 CuY)	LS	1		
		(Price in Words)				
		CONCRETE WORKS (approx. 86 CuY)				
29	C-01		LS	1		
		(Price in Words)				
30	AL-01	WINDOW W/ TYPE MARK 1 (approx. 1 EA)	LS	1		
		(Price in Words)				
31	AL-02	WINDOW W/ TYPE MARK 2 (approx. 2 EA)	LS	1		
		(Price in Words)				
32	AL-03	WINDOW W/ TYPE MARK 3 (approx. 1 EA)	LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
33	AL-04	WINDOW W/ TYPE MARK 4 (approx. 6 EA)	LS	1		
34	AL-05	DOOR W/ TYPE MARK 1 (approx. 2 EA) (Price in Words)	LS	1		
35	AL-06	DOOR W/ TYPE MARK 2 (approx. 1 EA) (Price in Words)	LS	1		
36	AL-07	DOOR W/ TYPE MARK 3 (approx. 4 EA) (Price in Words)	LS	1		
37	AL-08	DOOR W/ TYPE MARK 4 (approx. 1 EA) (Price in Words)	LS	1		
38	AL-09	DOOR W/ TYPE MARK 5 (approx. 2 EA) (Price in Words)	LS	1		

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
39	AL-10	DOOR W/ TYPE MARK 6 (approx. 1 EA)	LS	1		
		(Price in Words)				
		ALUMINUM THRESHOLD 6'- 3" x 4" (approx. 2 EA)				
40	DS-01		LS	1		
		(Price in Words)				
41	DS-02	ALUMINUM THRESHOLD 3'- 4" x 7" (approx. 1 EA)	LS	1		
		(Price in Words)				
		MARBLE SADDLE 3'-4"X 7" (approx. 7 EA)				
42	DS-03		LS	1		
		(Price in Words)				
43	STL-01	STEEL GUARDRAIL+HANDRAIL (approx. 85b LF)	LS	1		
		(Price in Words)				
		ACOUSTIC TILES (approx. 214 SF)				
44	AC-01		LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
		LIGHTING FIXTURE MARK L-1 (approx. 10 EA)				
45	L-01		LS	1		
		(Price in Words)				
		LIGHTING FIXTURE MARK L-2 (approx. 19 EA)				
46	L-02		LS	1		
		(Price in Words)				
		LIGHTING FIXTURE MARK L-3 (approx. 16 EA)				
47	L-03		LS	1		
		(Price in Words)				
		LIGHTING FIXTURE MARK L-4 (approx. 5 EA)				
48	L-04		LS	1		
		(Price in Words)				
		EMERGENCY LIGHTING FIXTURE MARK EM-1 (approx. 3 EA)				
49	L-05		LS	1		
		(Price in Words)				
		EMERGENCY LIGHTING FIXTURE MARK EM-2 (approx. 4 EA)				
50	L-06		LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
51	L-08	EXIT LIGHTING FIXTURE MARK EX-1 (approx. 2 EA)	LS	1		
	2 00					
		(Price in Words)				
		CEILING FAN W/ TYPE MARK CF-1 (approx. 2 EA)				
52	L-07		LS	1		
		(Price in Words)				
		EXTERIOR AND INTERIOR SCIP WALLS (approx. 92 CY)				
53	SCP-01		LS	1		
		(Price in Words)				
		EXTERIOR AND INTERIOR PAINT (approx. 10,709 SF)				
54	P-01		LS	1		
		(Price in Words)				
		GYPSUM WALLBOARD CEILING (approx. 125 SF)				
55	GB-01		LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
		WALL TILE W/ TYPE MARK WT-1 (approx. 630 SF)				
56	WT-01		LS	1		
		(Price in Words)				
57	D 04	EXTERIOR AND INTERIOR PAINT (approx. 10,709 SF)	LS	4		
57	P-01		LS	1		
		(Price in Words)				
		ACCOUSTIC TILES (approx. 214 SF)				
58	AC-01		LS	1		
		(Price in Words)				
		GYPSUM WALLBOARD CEILING (approx. 125 SF)				
59	GB-01		LS	1		
		(Price in Words)				
		WALL TILE W/ TYPE MARK WT-1 (approx. 630 SF)				
60	WT-01		LS	1		
		(Price in Words)				
		WALL BASE W/ TYPE MARK WB-1 (approx. 310 LF)				
61	WB-01		LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
62	RF-01	FLOOR MOUNTED TOILET (approx. 3 EA)	LS	1		
		(Price in Words)				
63	RF-02	UNDER MOUNTED SINK (approx. 3 EA)	LS	1		
		(Price in Words)				
64	RF-03	SINK FAUCET (approx. 3 EA)	LS	1		
		(Price in Words)				
65	RF-04	BOTTLE TRAP (approx. 3 EA)	LS	1		
		(Price in Words)				
66	RF-05	36" GRAB BAR (approx. 1 EA)	LS	1		
		(Price in Words)				
67	RF-06	42" GRAB BAR (approx. 1 EA)	LS	1		
		TOILET TISSUE DISPENSER (approx. 3 EA)				
68	RF-07		LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
69	RF-08	BABY CHANGING STATION (approx. 1 EA)	LS	1		
		(Price in Words)				
70	RF-09	FOAM SOAP DISPENSER (approx. 3 EA)	LS	1		
		(Price in Words)				
71	RF-10	WASTE RECEPTACLE (approx. 2 EA)	LS	1		
		(Price in Words)				
72	RF-11	AUTOMATIC HAND DRYER (approx. 3 EA)	LS	1		
		(Price in Words)				
73	RF-12	LED BACKLIT MIRROR (approx. 2 EA)	LS	1		
74	RF-13	TILT MIRROR W/ STAINLESS STEEL FRAME (approx. 1 EA) (Price in Words)	LS	1		
75	SS-1	SOLID SURFACE-SINK (approx. 3 EA) (Price in Words)	LS	1		

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
76	OE-02	AIRPORT WAITING CHAIRS 2 BENCHES W/ 3 CHAIRS (approx. 1 EA)	LS	1		
		(Price in Words)				
		METAL MESH SCREEN FOR AC UNIT (approx. 1 EA)				
77	OE-03		LS	1		
		(Price in Words)				
		EXTERIOR SIGNAGE W/AIRPORT NAME (approx. 1 EA)				
78	SIGN- 01		LS	1		
		(Price in Words)				
		INTERIOR RESTROOMS SIGNAGES (approx. 1 EA)				
79	SIGN- 02		LS	1		
		(Price in Words)				
		6" ROOF SLAB (approx. 50 CY)				
80	R-01		LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
		ROOF PARAPETS (approx. 156 CY)				
81	R-02		LS	1		
		(Price in Words)				
82	R-03	METAL FLASHINGS (approx. 209 LF)	LS	1		
				·		
		(Price in Words)				
		TPO ROOFING MEMBRANE (approx. 2,556 SF)				
83	R-04		LS	1		
		(Price in Words)				
		WALKING PATH (approx. 511 SF)				
84	R-05		LS	1		
		(Price in Words)				
		2" SCUPPER DRAINGE (approx. 4 EA)				
85	R-06		LS	1		
		(Price in Words)				
		OVERFLOW SCUPPER (approx. 5 EA)				
86	R-07		LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
87	R-07	LADDER FOR ROOF ACCESS (approx. 1 EA)	LS	1		
		(Price in Words)				
88	R-08	ROOF HATCH (approx. 1 EA)	LS	1		
		(Price in Words)				
89	ES-01	ADJUSTMENT OF PREPA/LUMA FACILITIES	LS	1		
		(Price in Words)				
90	ES-02	CONCRETE POLES, H4, 45 FT. (approx. 9 EA)	LS	1		
		(Dries in Monde)				
91	ES-03	(Price in Words) CONCRETE POLES, H4, 40 FT. (approx. 5 EA)	LS	1		
		(Price in Words)				
92	ES-04	PREPA/LUMA DISTRIBUTION STANDARDS, CP-A6 (approx. 8 EA)	LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
93	ES-05	PREPA/LUMA DISTRIBUTION STANDARDS, E-1-2-3 (approx. 1 EA)	LS	1		
		(Price in Words)				
94	ES-05	PREPA/LUMA DISTRIBUTION STANDARDS, E-1-2-3 (approx. 1 EA)	LS	1		
		(Price in Words)				
95	ES-06	PREPA/LUMA DISTRIBUTION STANDARDS, F-1-3 (approx. 1 EA)	LS	1		
		(Price in Words)				
96	ES-07	PREPA/LUMA DISTRIBUTION STANDARDS, F-1-3 (approx. 1 EA)	LS	1		
		(Price in Words)				
97	ES-08	PREPA/LUMA DISTRIBUTION STANDARDS, K-5 (approx. 2 EA)	LS	1		
		(Price in Words)				
98	ES-09	PREPA/LUMA DISTRIBUTION STANDARDS, K-6 (approx. 8 EA)	LS	1		
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
99	ES-10	PREPA/LUMA DISTRIBUTION STANDARDS, K-7-2 (approx. 1 EA)	LS	1		
99	ES-10		LS	I		
		(Price in Words)				
400	50.44	PREPA/LUMA DISTRIBUTION STANDARDS, STL-10 (approx. 19 EA)		_		
100	ES-11		LS	1		
		(Price in Words)				
		CONDUCTOR, #4/0 AWG, CU, XHHW-2, 600V (approx. 111 LnM)				
101	ES-12		LS	1		
		(Price in Words)				
		CONDUCTOR, #4/0 AWG, CU, XHHW-2, 600V (approx. 111 LnM)				
102	ES-13		LS	1		
		(Price in Words)				
		CONDUCTOR, #3/0 AWG, CU, XHHW-2, 600V (approx. 126 LnM)				
103	ES-14		LS	1		
		(Price in Words)				
		CONDUCTOR, #6 AWG, CU, XHHW-2, 600V (approx. 42 LnM)				
104	ES-15		LS	1		
		(Price in Words)				
		(Price in Words)				

Bid Item	Item No.	Item Description & Unit Price Bid In Words	Unit	Est. Quant.	Unit Price	Total Amount Per Item
405	50.40	CONDUIT, 3 IN. DIA, PVC SCH 40 (approx. 395 LnM)	. 0			
105	ES-13		LS	1		
		(Price in Words)				
		POWER SUBSTATION, 37.5KVA, 1PH, 240/120V (approx. 1 EA)				
106	ES-14		LS	1		
		(Price in Words)				
		REMOVAL OF LUMA EXISTING FACIL.				
107	ES-15		LS	1		
		(Price in Words)				
		30 KVA/240V EMERGENCY DIESEL GENERATOR W/ATS, BAT. CHGR. AND SUBBASE FUEL TANK (approx. 1 EA)				
108	ES-16		LS	1		
		(Price in Words) LUMA CONNECTION ALLOWANCE				
		(approx. 1 EA)				
109	ES-18	**************************************	LS	1	\$10,000.00	\$10,000.00
		(Price in Words)				
		MAIN TERMINAL BUILDING ELECTRICAL WORKS WITH DISTRIBUTION PANEL, METER SOCKET BOX AND LUMA CONN.				
110	1E-01		LS	1		
		(Price in Words)				

111	1E-02	MAIN TERMINAL PHOTOVOLTAIC PANELS SYSTEM, 22KW WITH INVERTER (approx. 1 EA) (Price in Words)	LS	1		
112	1E-03	MAIN TERMINAL BATTERY STORAGE, 13.5KWH (approx. 2 EA) (Price in Words)	LS	1		
113	1E-04	MAIN TERMINAL BUILDING FIRE ALARM SYSTEM (approx. 1 EA) (Price in Words)	LS	1		
114	1E-04	MAIN TERMINAL BUILDING TELECOMM. COUNDUITS AND ACCESSORIES		1		
115	2E-01	(Price in Words) HANGAR 2 ELECTRICAL WORKS W/DISTRIBUTION PANEL AND METER SOCKET BOX PEDESTAL (Price in Words)		1		
116	2E-02	(Price in Words) AIRFIELD LIGHTS EQUIPMENT REPLACEMENT ALLOWANCE (approx. 1 EA) ***********************************		1	\$15,000.00	\$15,000.00

		FURNISHING AND INSTALLING LIGHTNING PROTECTION SYSTEM (approx. 1 EA)				
117	2E-03	**************************************	LS	1	\$20,000.00	\$20,000.00
		(Price in Words)				

TOTAL BASE BID. (Shall include the <u>SUM</u> of all partial pricing, from item No. 1 to item No. 117, inclusive.) Write <u>TOTAL BASE BID</u> amount in words:	
	\$
(In case of discrepancy the amount shown in words shall govern.)	

It is understood that the above total price is for the entire work as required by the Drawings and Technical Specifications, that the price include all labor, equipment, materials, taxes, bailing, incidental work, overhead, profit, insurance, etc. to cover the finished work of the several kinds called for under the Contract, of which this Proposal is part. If a portion of the work shown in the drawings does not have specific line item, include the costs in the most related item.

The Contractor (Bidder) irrevocably accepts that the contract cost in the base Proposal includes any and all overhead cost (job site, project fixed overhead, field office and extended main office overhead) and any profit that the Contractor may incur for up to forty-five (45) calendar days of delays caused by any act of the Owner. The Contractor waives any type of claim for the overhead incurred during that period.

Bidder hereby agrees to commence works under this contract on a date to be specified in written "Notice to Proceed" of PRPA and to fully complete all works within **three hundred sixty (360) consecutive calendar days** after written "Notice to Proceed" of the Puerto Rico Ports Authority.

Time for substantial completion shall be **two hundred sixty (260) consecutive calendar days** subject to any extension of time that may be granted, in accordance with Article 9.1.4 of the Uniform General Conditions. Date of substantial completion will be certificated by the Owner, when in the opinion of the Owner all Work is completed. Merely the eventual use or partial utilization of the areas by the Owner does not constitute substantial completion. Substantial completion will occur when the Owner's representative has certified that all components of the works including mechanical, electrical, plumbing, fire suppression, security and data systems are fully functional, and have been tested and accepted.

Bidder further agrees to pay as liquidated damages for the amount established in section 9.5 of the Uniform General Conditions base on the Bid Price for each calendar day that the project construction, included in the combination accepted by the owner, remains uncompleted after the time frame from the date of the order to proceed with the construction for each calendar thereafter as hereinafter provided in Section 9.4.1 of the Uniform General Conditions.

The cost bellow will be the project fixed overhead or field office cost to be reimbursed to the Contractor by the Owner due to time extensions, delays, or interruptions to the work caused by any act of the Owner in excess of thirty (30) calendar days, as per Uniform General Condition 9.3 Delays and Extension of Time.

Item	Description	Units	Unit Price
1a	**FIELD OFFICE / MAIN OFFICE EXTENDED OVERHEAD CAUSED BY DELAYS AND EXTENSION OF TIME BY THE OWNER As per Uniform General Condition 9.3 Delays and Extension of Time.	Per Day	\$(Write Price in Words)

^{**}Under no circumstance will the amount of Adjustment for Extended Overhead caused by delays and extension of time by the Owner will exceed the amount of liquidated damages as per section 9.5 of the Uniform General Conditions, Damages and amount calculated per Eichleay formula in accordance to Uniform General Condition 15.1.1.1.7.

The Bidder agrees that this bid shall be valid and may not be withdrawn for a period of one hundred eighty (180) calendar days after the scheduled closing time for receiving bids. Upon receipt of written notice of the acceptance of this bid, the Bidder will execute the formal contract included in the Contract Documents within ten (10) working days and deliver the required insurance and bonds specified in the General Conditions.

The Bidder acknowledges receipt of the following addenda:

Addendum No.	_ dated
Addendum No.	
Addendum No.	dated
Addendum No.	

The Bidder understands that the Puerto Rico Ports Authority reserves the right to reject any or all bids and to waive any informalities in the bidding process.

EQUAL OPPORTUNITY REPORT STATEMENT

(Complete the following statement by checking the appropriate boxes. Failure to complete these

boxes may be grounds for rejection of bid):

- 1. The Bidder has / / has not / / developed and has on file at each establishment affirmative action programs pursuant to 41 CFR 60-1.40 and 41 CFR 60-2.
- 2. The Bidder has / / has not / / participated in any previous contract or subcontract subject to the equal opportunity clause prescribed by Executive Order 11246, as amended.
- 3. The Bidder has / / has not / / filed with the Joint Reporting Committee the annual compliance report on Standard Form 100 (EE-1 Report).
- 4. The Bidder does / / does not / / employ fifty (50) or more employees.

CERTIFICATION OF NONSEGREGATED FACILITIES

By the submission of this bid, the Bidder, offer or, applicant, or subcontractor certifies that he does not maintain or provide for his employees any segregated facilities at any of his establishments and that he does not permit his employees to perform their services at any location, under his control, where segregated facilities are maintained. He certifies further that he will not maintain or provide for his employees any segregated facilities at any of his establishments and that he will not permit his employees to perform their services at any location under his control, where segregated facilities are maintained.

The Bidder, offer or, applicant, or subcontractor agrees that a breach of this certification is a violation of the Equal Opportunity clause in this contract. As used in this certification the term "segregated facilities" means any waiting rooms, work areas, rest rooms and wash rooms, restaurants and other eating areas, time clocks, locker rooms and other storage or dressing areas, parking lots, drinking fountains, recreation or entertainment areas, transportation, and housing facilities provided for employees which are segregated by explicit directive or are in fact segregated on the basis of race, color, religion, or national origin, because of habit, local custom, or otherwise. He further agrees that (except where he has obtained identical certifications from proposed subcontractors for specific time periods) he will obtain identical certifications from proposed subcontractors prior to the award of subcontracts exceeding \$10,000 which are not exempt from the provisions of the Equal Opportunity clause; that he will retain such certifications in his files and that he will forward the following notice to such proposed subcontractors (except where the proposed subcontractors have submitted identical certifications for specified time periods):

NOTICE TO PROSPECTIVE SUBCONTRACTORS OF REQUIREMENT FOR CERTIFICATIONS OF NONSEGREGATED FACILITIES


A certification of Non-segregated Facilities must be submitted prior to the award of a subcontract exceeding \$10,000.00 which is not exempt from the provisions of the Equal Opportunity clause.


The certifications may be submitted either for each subcontract or for all subcontractors during a period (i.e., quarterly, semiannually, or annually).


NOTE: The penalty for making false statements in offers is prescribed in 18 U.S.C. 1001.


The bid bond (five percent (5%) of the bid amount) will become property of the Puerto Rico Ports Authority in the event that the contract and bonds are not executed within the time set forth.


Respectfully submitted:	
Name of Bidder *(Corporation, Partnership, or Individual)	
Ву:	Address
Name of Authorized Officer	Signature of Authorized Officer
Tel. No.:	
Cell No.:	





























DOOR SCHEDULE							
Type Mark	Count M	odel Comments	Height	Width	Operation	Description	
1	2		10' - 0''	18' - 0''	RLH/RRH		
2	1		7' - 0''	6' - 9''	RLH/RRH		
3	4		7' - 0''	3' - 4"	LH	HOLLOW METAL DOOR WITH STEEL FRAME, LOUVER AND STAINLESS-STEEL KICK PLATE.	
4	1		7' - 0''	3' - 4''	RH	HOLLOW METAL DOOR WITH STEEL FRAME, LOUVER AND STAINLESS-STEEL KICK PLATE.	
5	2		7' - 0''	3' - 3"	RRH		
7	1 ESD20	COOKSON/CORNELL ROLLING DOORS	3 11' - 9"	25' - 0''	ROLLUP	BUILT TO ORDER METAL SLATTED ROLLING DOORS PROVIDE SECURITY AGAINST ENTRY AND/OR WEATHER PROTECTION.	

				WINDOV	V SCHEDULE
Type Mark	Count	Height	Width	Material	Description
1	1	5' - 9"	5' - 4"		
2	2	1' - 8 3/4"	10' - 7 5/8"		
3	1	1' - 8 3/4"	10' - 7 5/8"		
4	6	6' - 6"	15' - 0''		
Grand total: 10					

		HARDWARE SET 1		
		DOOR TYPE: #3, #4		
3 ea	HINGES	4.5 X 4.5 -BAA 5BB1 4.5 X 4.5 US	US32D	IVES
1 ea	CYLINDRICAL LOCKSET	ND40	US26D	SCHLAGE
1 ea	DOOR CLOSER	REGULAR ARM-4040XP REG 689 STD SRT		LCN
3 ea	SILENCERS	SR64		IVES
1 ea	FLOOR DOORSTOP	FS13	US26D	IVES
		HARDWARE SET 2		
		DOOR TYPE: #5		
3 ea	HINGES	4.5 X 4.5 -BAA 5BB1 4.5 X 4.5 US	U\$32D	IVES
1 ea	EXIT DEVICE W/ FUNCTION	L-DT 25 R SERIES	US26D	FALCON
1 ea	DOOR CLOSER	REGULAR ARM-4040XP REG 689 STD SRT		LCN
3 ea	SILENCERS	SR64		IVES

<u>RCMDO</u>	RCMDO ARQUITECTOS PSC 316 DE DIEGO AVENUE, SUITE 201 SAN JUAN, PR 00909
ENGINEED	

LADISLAO ORTIZ & ASOCIADOS INGENIEROS, CSP 334 AVE. AMERICO MIRANDA, SAN JUAN, PUERTO RICO 00927-0122 T: 787.767.7337 F: 787.767.7636



SBM'T:	
XXXXXXXX	DATE
CHIEF OF STUDIES AND DESIGNS	
RCM'D:	
ROMEL PEDRAZA, PE	DATE
ASST. EXEC. DIR. ENG., CONST. & PLAN	
APP'D:	
NORBERTO J. NEGRÓN DÍAZ, ESQ.	DATE
EXECUTIVE DIRECTOR	

			· · · · · · · · · · · · · · · · · · ·
NO.	DATE	ISSUE DESCRIPTION	BY
3	10.22.2025	ISSUE FOR BIDDING	
		1	

DR-4339-PR HURRICANE MARIA DISASTER RECOVERY MPPA057 HUMACAO REGIONAL AIRPORT (HUC) HUMACAO, PUERTO RICO

DOORS & WINDOWS SCHEDULE

PRPA PROJ NO:	
DRAWN BY:	
DESIGNED BY:	
CHECKED BY:	
DATE:	
SCALE:	Н
SHEET NO.	

1A-6.1

